




# Polycom® Conference Phone Guide



	IP Conference Phones					USB-Conference
	Large Room	Standard Conference Room			Small Room and Office	
	SoundStation IP 7000 	SoundStation Duo 	CX3000 	SoundStation IP 6000 	SoundStation IP 5000 	SS Connect 
<b>Connection</b>						
Analog		•				
IP (SIP)	•	•		•	•	
Microsoft® Lync™		•	optimized		•	•
USB						•
<b>Voice Quality</b>						
Polycom HD Voice™ technology	•	•	•	•	•	•
Loudspeaker frequency response	160Hz – 22kHz	220Hz – 7kHz	200Hz – 7kHz	220Hz – 14kHz	250Hz – 7kHz	300Hz – 7kHz
Microphone pickup range	6m/20ft	3m/10ft	3.6m/12ft	3.6m/12ft	2m/7ft	2m/7ft
Intelligent microphone mixing	•	•	•	•	•	•
Dynamic noise reduction	•	•	•	•	•	•
Automatic gain control	•		•	•		•
<b>Additional Features</b>						
Resists interference from wireless devices	•	•	•	•		•
Software upgradable	•	•	•	•		•
Large display to support advanced applications	•		•			
Multi-unit connectivity	•					
Connect to external audio system	• <sup>(1)</sup>					•
Computer/mobile device connectivity	•				•	• <sup>(2)</sup>
<b>Optional Accessories</b>						
Expansion microphones (wired)	•	•	•	•		
Wireless lapel pin microphone	•(NA only)			•(NA only)		
Video integration kit or cables	•					
Computer calling kit		•				
Mobile device cables	•	•				
<b>Model Variants</b>						
Power over Ethernet (PoE)	2200-40000-001		2200-15810-025	2200-15600-xxx	2200-30900-025	
AC or Power over Ethernet (PoE)	2230-40300-001	2200-19000-xxx		2200-15660-xxx	2200-30900-xxx	
USB Powered						2200-44900-xxx

<sup>1</sup> Optional accessory required

<sup>2</sup> Devices with powered USB

## Analog Conference Phones

### Large Room

SoundStation VTX 1000



### Standard Conference Room

SoundStation2™



SoundStation Duo™



SoundStation2W



### Small Room and Office

VoiceStation 500



VoiceStation 300



#### Network Connectivity

Analog	•	•	•	•	•	•
IP (SIP)			•			
Microsoft® Lync™			•			
Digital PBX		• <sup>(1)</sup>				

#### Voice Quality

Polycom HD Voice™ technology			•			
Loudspeaker frequency response	80Hz – 7kHz <sup>(3)</sup>	300Hz – 3300Hz	220Hz – 7kHz	300Hz – 3500Hz	300Hz – 3300Hz	300Hz – 3300Hz
Microphone pickup range	6m/20ft	3m/10ft	3m/10ft	3m/10ft	2m/7ft	2m/7ft
Intelligent microphone mixing	•	•	•	•	•	•
Dynamic noise reduction	•	•	•	•	•	•
Automatic gain control	•					

#### Additional Features

Resists interference from wireless devices	•	•	•	•	•	•
Software upgradable	•		•	•		
Large display to support advanced applications						
Multi-unit connectivity						
Connect to external audio system	•	•		•		
Bluetooth connectivity						

#### Optional Accessories

Expansion microphones (wired)	•	• <sup>(2)</sup>	•	• <sup>(2)</sup>		
Wireless lapel pin microphone	•	•				
Video integration kit or cables	•					
Computer calling kit		• <sup>(2)</sup>	•	• <sup>(2)</sup>	•	
Mobile device cables		• <sup>(2)</sup>	•	• <sup>(2)</sup>	•	

#### Model Variants

	2200-07142-xxx (with EX mics only)	2200-15100-xxx (non expandable w/o display)	2200-19000-xxx	2200-07800-xxx (Expandable)	2200-17900-xxx	2200-17910-xxx
	2200-07300-xxx (w/o EX mics and subwoofer)	2200-16000-xxx (non- expandable, w/display)		2200-07880-xxx (Basic)		
	2200-07500-xxx (with subwoofers only)	2200-16200-xxx (expandable, w/display)				

<sup>1</sup> Models available with integration to selected digital PBX. See product details for more information.

<sup>2</sup> Available on selected models

<sup>3</sup> SoundStation VTX to SoundStation VTX